

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

Final Progress Report for
NASA Grant 1262



I. Summary of Progress

The support provided by this grant has contributed to the development of a vortex-lattice method that can accurately model general unsteady lifting and nonlifting flows and to the partial development of a continuous-vorticity panel method. Applications of these methods to lifting surfaces are not restricted by planform, camber, twist, or angle of attack as long as separation occurs only along sharp edges and vortex-bursting does not occur near the lifting surface.

The initial goal under this support was to develop a method for modelling steady lifting flows over highly swept delta wings at large incidence. The experimental observations of Peckham¹ and Marsden, Simpson, and Rainbird,² among others, showed the aerodynamic characteristics to be independent of Reynolds number, suggesting an inviscid model would be adequate. After making an exhaustive review of literature that included the innovative, but inadequate, attempts of Brown and Michael³ and Mangler and Smith,⁴ we decided to attempt development of a vortex-lattice method. To demonstrate the feasibility of using such a method, we modified an existing code developed by Giesing, Kalman, and Rodden.⁵ We added a system of vortex lines to simulate the leading-edge wake. This work is described in the M.S. thesis of S. A. Maddox⁶ and in the Journal of Aircraft.⁷ The coefficients predicted by the modified code were in good agreement with experimental data. And it was found that in a Trefftz plane the centroid of the circulations in the leading-edge vortex system nearly coincided with the experimentally determined

VIRGINIA POLYTECHNIC INSTITUTE AND STATE UNIVERSITY

Blacksburg, Virginia 24061

NB3-16284

Unclass
02483

(NASA-CR-169749) SUBSONIC STEADY AND
UNSTEADY AERODYNAMIC LOADS ON MISSILES AND
AIRCRAFT Final Progress Report (Virginia
Polytechnic Inst. and State Univ.) 8 p
HC A02/MF A01 CSCL 01A G3/02

core of the leading-edge wake, indicating that the geometry of the wake is adequately represented.

Though these results were generally in good agreement with the experimental data, the scheme of Giesing et al. for placing elements on the wing was not well-suited for low-aspect delta wings. Moreover, the geometry of the wake attached to the trailing edge had been ignored. Consequently, several entire new codes were developed. These treated delta, rectangular, and swept wings. This work was reported in the Ph.D. thesis of O. A. Kandil⁸ and in the Journal of Aircraft.⁹ Subsequently, the capability of modelling steady aerodynamic interference was demonstrated by Kandil, Mook, and Nayfeh.^{10,11}

The success of the method for steady flows led us to attempt development of a general unsteady, vortex-lattice method. The first progress in this area was described in the M.S. thesis of E. H. Atta¹² and in references 13 and 14. Originally, the problem was posed in terms of a ground-fixed reference frame, a scheme that proved to be awkward. Subsequently the method was modified so that the problem was posed in terms of a body-fixed reference frame. This progress was reported in the M.S. thesis of D. F. Thrasher,¹⁵ and in reference 16 flows past rectangular wings were treated. Kandil, Atta, and Nayfeh¹⁷ used the body-fixed formulation and treated flows past delta wings.

Subsequently, the method was considerably refined in the M.S. thesis of P. Konstadinopoulos.¹⁸ The final version has been used to treat flows past helicopter rotors, rolling and pitching wings, with, and without, flaps. A manuscript has been submitted to the AIAA and is now under review.

In an attempt to treat small oscillations of wings about arbitrary angles of incidence, Mayfeh, Mook, and Yen used perturbation theory to obtain an easily solved linear problem for the real and imaginary parts of the fluctuating loads. This work was reported in reference 19. It was found, however, that the general method is just as efficient at treating this problem. The results obtained by the general method agreed with those obtained by the perturbation method.

The method was then extended to treat bodies and wing-body combinations. Progress was reported in the M.S. thesis of K. R. Asfar,²⁰ in the Ph.D. thesis of E. H. Atta²¹ and in references 22 and 23.

The next and final effort under this grant is being directed toward the development of a continuous-vorticity panel method. With this method the strong, undesirable algebraic singularities associated with the Biot-Savart law are removed. However, continuous panels lead to a noticeable increase in complexity and place more demands on the capabilities of the computer and the programmer; the price is high. Progress in this area was recently reported in the Ph.D. thesis of A. Yen²⁴ and in reference 25. Continuous, triangular panels of vorticity were used to model a delta wing and its leading-edge and trailing-edge wakes, and to model a rectangular wing and its wing-tip vortex systems. The results for total loads are in excellent agreement with previous solutions and experimental data. The calculated vorticity field lines are realistic, and most importantly, the flow field is nearly devoid of singularities. When the continuous panels become tightly rolled in the wake, they are merged into a concentrated vortex core. The locations and strength of the entire wake, including the vortex core formed by the merger, are obtained as part of the solutions.

More recently, M. Kim has used the continuous-panel method (now using both sources and vorticity for comparisons of complexity, accuracy, etc.) to obtain solutions for flows around three-dimensional non-lifting bodies. These preliminary results agree with exact solutions and other solutions obtained numerically by the Douglass-Neumann program. A two-dimensional, thick airfoil has recently been treated, and preliminary designs of computer codes for general unsteady flows over airfoils and thick, three-dimensional wings have been completed. This work will be contained in Mr. Kim's doctoral dissertation.

II. Summary of Graduate Students Receiving Support

1. S. A. Maddox, M.S. 1973, after graduation worked several years for Lockheed, and currently is an attorney in the State of Washington.
2. O. A. Kandil, Ph.D. 1974, after graduation remained at VPI as an assistant professor, and currently is an associate professor at Old Dominion University.
3. E. H. Atta, M.S. 1976 and Ph.D. 1978, has worked at Lockheed Marietta since graduation, recently spent a year at NASA-Ames, and currently is doing research in transonic flows.
4. S. G. Kelley, M.S. 1978, systematically examined the influence of panel shape, size, etc. on the accuracy of the vortex-lattice method, and currently is an assistant professor at University of Notre Dame.
5. K. R. Asfar, M.S. 1978, is currently an assistant professor at Yarmouk University, Irbid, Jordan.

6. D. F. Thrasher, M.S. 1979, is currently completing his Ph.D. while working at the David Taylor Naval Ship Research and Development Center, and is applying the vortex-lattice method to model separated flows past submarines making turns.
7. P. Konstadinopoulos, M.S. 1981, is currently completing his Ph.D. requirements.
8. A. Yen, Ph.D. 1982, is currently working for General Motors. (Due to problems with citizenship, security, etc. Dr. Yen had difficulty finding employment in the aerospace industry.)
9. M. Kim will complete his Ph.D. in 1983.

III. Applications of the Method Outside the Aerospace Community

D. Thrasher is applying the technique to treat submarines, eventually hoping to obtain loads on the hull, sail and diving planes during a maneuver.

D. F. Greely, in a recent Ph.D. thesis at MIT*, used the vortex-lattice method, giving reference to publications cited here, to model the flow through the propeller of a ship, finding excellent agreement with experimental data for thrust and torque.

IV. Acknowledgement

We take this opportunity to express our appreciation and gratitude to NASA for supporting the research described above. A special word is due Dr. E. C. Yates, the grant monitor; his support and contributions made through numerous technical discussions are gratefully acknowledged.

*"Marine Propeller Blade Tip Flows," Ph.D. Thesis, Dept. Ocean Engineering, Massachusetts Institute of Technology, January 1982.

References

1. Peckham, D. H., "Low-speed wind-tunnel tests on a series of uncambered slender pointed wings with sharp edges," ARC R & M No. 3186, 1958.
2. Marsden, D. K., Simpson, R. W., and Rainbird, B. E., "An investigation into the flow over delta wings at low speeds with leading-edge separation," College of Aeronautics, Cranfield, Report No. 114, 1958.
3. Brown, C. W. and Michael, W. H., "On slender delta wings with leading-edge separation," NACA TN 3430, 1955.
4. Mangler, K. W. and Smith, J. H. B., "Calculation of flow past slender delta wings with leading-edge separation," RAE Report No. 2593, 1957.
5. Giesing, J. P., Kalman, T. P., and Rodden, W. P., "Subsonic unsteady aerodynamics for general configurations," USAF FDL-TR-71, 1971.
6. Maddox, S. A., "An extension of a vortex-lattice method to include the effects of leading-edge separation," M.S. Thesis, Dept. Engineering Science and Mechanics, Virginia Polytechnic Institute and State University, Blacksburg, VA, 1973.
7. Mook, D. T. and Maddox, S. A., "Extension of a vortex-lattice method to include the effects of leading-edge separation," J. Aircraft, 11, p. 127, 1974.
8. Kandil, O. A., "Prediction of the steady aerodynamic loads on lifting surfaces having sharp-edge separation," Ph.D. Thesis, Dept. Engineering Science and Mechanics, Virginia Polytechnic Institute and State University, Blacksburg, VA, 1974.
9. Kandil, O. A., Mook, D. T., and Nayfeh, A. H., "Nonlinear prediction of the aerodynamic loads on lifting surfaces," J. Aircraft, 13, p. 22, 1976.
10. Kandil, O. A., Mook, D. T., and Nayfeh, A. H., "Application of the nonlinear vortex-lattice concept to aircraft interaction problems," NASA CP-7001, p. 1321, 1976.
11. Kandil, O. A., Mook, D. T., and Nayfeh, A. H., "A numerical technique for computing subsonic flow past three-dimensional canard-wing configurations with edge separation," AIAA paper No. 77-1, 1977.
12. Atta, E. H., "Unsteady flow over arbitrary planforms including tip separation," M.S. Thesis, Dept. Engineering Science and Mechanics, Virginia Polytechnic Institute and State University, Blacksburg, VA, 1976.

13. Atta, E. H., Kandil, O. A., Mook, D. T., and Nayfeh, A. H., "Unsteady flow past wings having sharp-edge separation," NASA SP-405, p. 407, 1976.
14. Atta, E. H., Kandil, O. A., Mook, D. T., and Nayfeh, A. H., "Nonlinear unsteady aerodynamic loads on rectangular and delta wings," AIAA paper no. 77-156, 1977.
15. Thrasher, D. F., "Nonlinear unsteady aerodynamics with application to dynamic-aerodynamic interaction," M.S. Thesis, Dept. Engineering Science and Mechanics, Virginia Polytechnic Institute and State University, Blacksburg, VA, 1979.
16. Thrasher, D. F., Mook, D. T., Kandil, O. A., and Nayfeh, A. H., "Application of the vortex-lattice concept to general, unsteady lifting surface problems," AIAA paper no. 77-1157, 1979.
17. Kandil, O. A., Atta, E. H., and Nayfeh, A. H., "Three dimensional steady and unsteady asymmetric flow past wings of arbitrary planform," paper no. 2, AGARD Fluid Dynamics Panel Symposium, Ottawa, Canada, 1977.
18. Konstadinopoulos, P., "A vortex-lattice method for general unsteady subsonic aerodynamics," M.S. Thesis, Dept. of Engineering Science and Mechanics, Virginia Polytechnic Institute and State University, Blacksburg, VA, 1981.
19. Nayfeh, A. H., Mook, D. T., and Yen, A., "The aerodynamics of small harmonic oscillations around large angles of attack," AIAA paper no. 79-1520, 1979.
20. Asfar, K. R., "Application of the vortex-lattice technique to arbitrary bodies," M.S. Thesis, Dept. of Engineering Science and Mechanics, Virginia Polytechnic Institute and State University, Blacksburg, VA, 1978.
21. Atta, E. H., "Nonlinear steady and unsteady aerodynamics of wings and wing-body combinations," Ph.D. Thesis, Department of Engineering Science and Mechanics, Virginia Polytechnic Institute and State University, Blacksburg, VA, 1978.
22. Asfar, K. R., D. T. Mook, and A. H. Nayfeh, "Application of the vortex-lattice technique to arbitrary bodies," AIAA paper no. 78-1205, 1978.
23. Atta, E. H. and A. H. Nayfeh, "Nonlinear aerodynamics of wing-body combinations," AIAA paper no. 78-1206, 1978.
24. Yen, A., "A continuous-vorticity panel method for the prediction of steady aerodynamic loads on lifting surfaces," Ph.D. Thesis, Department of Engineering Science and Mechanics, Virginia Polytechnic Institute and State University, Blacksburg, VA, 1982.

25. Yen, A., D. T. Mook, and A. H. Nayfeh, "A continuous-vorticity panel method for lifting surfaces," AIAA paper no. 81-1895, 1981. (A manuscript is being prepared for the AIAA Journal.)